



Material Safety Data Sheet

Infosafe No™ 2RM0S Issue Date : September 2013 ISSUED by RLA

Product Name **INTAFLOORS SPRAYABLE CONTACT ADHESIVE**

Classified as hazardous

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Name INTAFLOORS SPRAYABLE CONTACT ADHESIVE
Product Code IFA505
Product Use Sprayable contact adhesive.
Company Name INTAFLOORS GROUP
Address 15 Artisan Rd, Seven Hills, NSW 2147
Emergency Tel. AH 13 15 18
Telephone Tel: (02) 8678 5479
Number/Fax Fax: (02) 8678 5483
Other Information This MSDS summarises to the best of our knowledge the health and safety hazard information of the product and how to safely handle and use the product in the workplace.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Composition, information on ingredients Blend of polymers, solvents and additives.

Chemical Liquid

Characterization

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	Light aliphatic petroleum solvent	64742-49-0	30-60 %		
	Non Hazardous ingredients	Proprietary	10-30 %		
	Acetone	67-64-1	10-30 %		
	Toluene	108-88-3	10-30 %	Xn, F	R11, R20

3. HAZARDS IDENTIFICATION

Classified as hazardous according to NOHSC criteria.
Classified as a dangerous good according to the Australian Dangerous Good Code - 6th edition.

Chronic Effects Prolonged and repeated exposure through inhalation, ingestion or skin contact may result in harmful effects including central nervous system depression. Systemic effects of chronic exposure can also include damage to kidneys and liver, especially where exposure is repeated and prolonged with no personal protection.

Inhalation Excessive skin exposure may also result in irritation leading to dermatitis. Inhalation may lead to irritation of the respiratory system. Symptoms of overexposure may include fatigue, headache, drowsiness, shortness of breath and possible nausea. Very high concentrations of product vapour may cause central nervous system depression which can lead to loss of coordination, impaired judgement and if exposure is prolonged, unconsciousness and death.

Ingestion Ingestion may result in gastrointestinal irritation, in particular nausea, abdominal pain, vomiting and diarrhoea. Ingestion may also lead to aspiration of material into the lungs and central nervous system (CNS) depression. CNS effects include dizziness, drowsiness, confusion, headache, muscular weakness and loss of consciousness. Prolonged exposure to a large quantity can ultimately lead to coma and possibly death.

Skin Skin contact or solvent vapour will cause irritation including, itching, redness or rash. Prolonged and repeated exposure may cause skin dryness or cracking resulting in dermatitis.

Eye Eye contact and solvent vapour may cause moderate eye irritation. Symptoms may include redness, stinging, pain, tearing or swelling.

4. FIRST AID MEASURES

Inhalation Remove the source of contamination or move the victim to fresh air immediately. If not breathing apply artificial respiration at once and seek urgent medical advice. If irritation develops and persists, seek medical attention.

Material Safety Data Sheet

infosafe
CS: 1.7.2

Page: 2 of 5

Infosafe No™ 2RM0S Issue Date : September 2013 ISSUED by RLA

Product Name **INTAFLOORS SPRAYABLE CONTACT ADHESIVE**

Classified as hazardous

Ingestion	Do NOT induce vomiting. Seek immediate medical attention. For advice, contact a Poison Information Centre (Australia 13 1126) or a doctor at once.
Skin	Remove any contaminated clothing and wash affected areas thoroughly with soap and water. If irritation develops seek medical attention. Ensure contaminated clothing is washed before re-use or discard.
Eye	Immediately irrigate the contaminated eye(s) with plenty of water, holding the eyelid(s) open. If irritation develops and persists, seek medical attention.
First Aid Facilities	Eye wash fountain, safety shower and normal wash room facilities.
Advice to Doctor	Treat symptomatically. Extreme care must be taken to prevent aspiration.
Other Information	Exposure may aggravate existing conditions including skin sensitisation and dermatitis.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Wear full protective clothing and self contained breathing apparatus. Keep storage tanks cool with water spray as they may explode from heat of fire. Use foam, dry chemical or carbon dioxide extinguishers. Do NOT use water jet.
Specific Hazards	Fire/Explosion hazards: Product is flammable. Isolate from sources of heat, naked flames, sparks and strong oxidising materials. Take precautions against static electricity discharges. Earth and bond all process equipment. Ensure adequate ventilation to prevent an explosive vapour-air mixture. Vapours will travel considerable distances to sources of ignition and flash back. Remove sources of re-ignition.
Hazardous Combustion Products	Oxides of carbon, other organic compounds.
Flash Point	< 0 °C
Flammable Limits UEL	Not available.
Flammable Limits LEL	Not available.

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal	Evacuate area of all unnecessary people. Extinguish or remove all sources of ignition and shut off source of leak if safe to do so. Increase ventilation. Wear full protective equipment and clothing to minimise exposure. Contain the spill with inert, non combustible, absorbent material. Do not use combustible materials such as sawdust. Using non-sparking tools and equipment; collect the material and place into a suitable labelled and sealed container.
------------------------------	--

7. HANDLING AND STORAGE

Storage	Use only in a well ventilated area. Open containers cautiously as contents may be under pressure. Build up of mists or vapours in the atmosphere must be prevented. Avoid inhalation of vapours. DO NOT store or use in confined spaces. Prevent concentration in hollows and sumps. Do not enter these areas until atmosphere has been checked. Do not use near ignition sources. When dealing with large quantities, repeated or prolonged exposure with no personal protection should be avoided in order to lessen the possibility of disorders. It is essential that all who come into contact with this material, maintain high standards of personal hygiene ie.washing hands prior to eating, drinking, smoking or going to the toilet. Misuse of empty containers can be hazardous. Do not pressurise, cut, weld or drill empty containers as they may contain dangerous residues. Residues may ignite with explosive violence if heated sufficiently. Keep empty containers closed with bung in place. Store in a dry, cool, well ventilated area, away from ignition sources, heat, strong oxidising agents, foodstuffs and clothing. Keep containers closed when not in use and protected against physical damage. Inspect regularly for damage or leaks. Take precautions against static electricity discharges. Use proper grounding procedures. Have appropriate fire extinguishers available in and near areas of
----------------	---

Material Safety Data Sheet

infosafe
CS: 1.7.2

Page: 3 of 5

Infosafe No™ 2RM0S Issue Date : September 2013 ISSUED by RLA

Product Name **INTAFLOORS SPRAYABLE CONTACT ADHESIVE**

Classified as hazardous

storage and handling.
Reference should be made to all local, state and federal regulations as well as Australian Standards AS1940-The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Controls, Personal Protection	No National Occupational Health and Safety Commission (NOHSC) exposure standards are assigned to this product. However exposure standards for constituents are listed below. As with all chemicals, exposure should be maintained to the least possible levels.
National Exposure Standards	Toluene: TWA 50 ppm (191 mg/m ³); STEL 150 ppm (574 mg/m ³) Acetone: TWA 500ppm (1185 mg/m ³); STEL 1000 ppm (2375 mg/m ³) n-Hexane: TWA 20 ppm (72 mg/m ³); STEL None allocated
Respiratory Protection	Approved respirators may be necessary to prevent over exposure by inhalation. Available information suggests that an approved respirator with organic vapour filter may be suitable however will vary according to individual circumstances ie. actual airborne concentrations in local working environment. Hence the user should make the final assessment. Expert advice may be required to make this decision.
Eye Protection	Refer to AS/NZS 1715 - Selection, use & maintenance of respiratory protective devices and AS/NZS 1716 - Respiratory Protective Devices. To prevent eye contact, wear safety glasses, chemical goggles or face shield as appropriate. Refer to AS/NZS 1337 - Eye protectors for industrial applications.
Hand Protection	Impervious gloves recommended. Due to variations in glove construction and individual circumstances, the user should make a final assessment. Expert advice should be sought. Refer to AS/NZS 2161 Occupational protective gloves - Selection, use and maintenance.
Personal Protective Equipment	Avoid skin and eye contact. Avoid repeated and prolonged skin contact. Avoid inhaling the vapour, mist or dust. Do not smoke. Remove any naked lights or strong heat sources. Wearing of the following personal protective equipment may be advisable. Safety glasses, goggles or faceshield as appropriate. Overalls or similar protective apparel. Enclosed footwear. Organic vapour/acid mist respirator. Selection of the correct cartridge or canister is essential. Cartridges and canisters must be replaced regularly, frequency depending upon conditions of use. Chemically resistant gloves.
Body Protection	Wear impervious protective clothing to prevent skin contact. Discard or wash contaminated clothing before use.
Eng. Controls	The working environment must be adequately ventilated to maintain air concentrations to a minimum and below exposure limits especially where vapours or mists are generated; particularly in enclosed areas where natural ventilation is inadequate. A flame proof exhaust ventilation system or an approved respirator is recommended depending on assessment of local working environment. Product vapour is heavier than air and will collect at low levels. Hence, ventilate by extraction at low levels. For further information concerning ventilation, refer to: AS 1940 - The storage and handling of flammable and combustible liquids & AS2430 - Explosive gas atmospheres.
Other Information	Subsequent to handling product, do not eat or drink until after washing hands thoroughly.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Amber liquid.
Boiling Point	IBP: > 50 Degs.C.
Solubility in Water	Insoluble.
Specific Gravity (H₂O=1)	Approx. 0.83
Vapour Pressure	Not available.
Vapour Density (Air=1)	Not available.

Material Safety Data Sheet

infosafe
CS: 1.7.2

Page: 4 of 5

Infosafe No™ 2RM0S Issue Date : September 2013 ISSUED by RLA

Product Name **INTAFLOORS SPRAYABLE CONTACT ADHESIVE**

Classified as hazardous

Viscosity 300 - 400 cps
Colour Amber
Flash Point < 0 °C
Flammable Limits Not available.
LEL
Flammable Limits Not available.
UEL

10. STABILITY AND REACTIVITY

Stable under normal conditions of storage and handling.

Materials to Avoid Strong oxidising agents.

Hazardous Oxides of carbon.
Decomposition

Products

Hazardous Reaction Possible hazardous reaction with strong oxidising agents.

Conditions to Avoid Sources of ignition ie. flames.
Heat ie. direct sunlight.
Contact with incompatible materials.

11. TOXICOLOGICAL INFORMATION

Inhalation Inhalation may lead to irritation of the respiratory system. Symptoms of overexposure may include fatigue, headache, drowsiness, shortness of breath and possible nausea. Very high concentrations of product vapour may cause central nervous system depression which can lead to loss of coordination, impaired judgement and if exposure is prolonged, unconsciousness and death.

Ingestion Ingestion may result in gastrointestinal irritation, in particular nausea, abdominal pain, vomiting and diarrhoea. Ingestion may also lead to aspiration of material into the lungs and central nervous system (CNS) depression. CNS effects include dizziness, drowsiness, confusion, headache, muscular weakness and loss of consciousness. Prolonged exposure to a large quantity can ultimately lead to coma and possibly death.

Skin Skin contact or solvent vapour will cause irritation including, itching, redness or rash. Prolonged and repeated exposure may cause skin dryness or cracking resulting in dermatitis.

Eye Eye contact and solvent vapour may cause moderate eye irritation. Symptoms may include redness, stinging, pain, tearing or swelling.

Chronic Effects Prolonged and repeated exposure through inhalation, ingestion or skin contact may result in harmful effects including central nervous system depression. Systemic effects of chronic exposure can also include damage to kidneys and liver, especially where exposure is repeated and prolonged with no personal protection.
Excessive skin exposure may also result in irritation leading to dermatitis.

12. ECOLOGICAL INFORMATION

Information on Avoid contaminating waterways.
Ecological Effects

13. DISPOSAL CONSIDERATIONS

Conform to all local, state or federal regulations and guidelines for waste disposal. Do not flush or allow spillage to enter drains; sewers or watercourses-inform the local authority and the Environmental Protection Authority if this occurs.

14. TRANSPORT INFORMATION

U.N. Number 1133
Proper Shipping ADHESIVES
Name
DG Class 3

Material Safety Data Sheet

infosafe
CS: 1.7.2

Page: 5 of 5

Infosafe No™ 2RM0S Issue Date : September 2013 ISSUED by RLA

Product Name **INTAFLOORS SPRAYABLE CONTACT ADHESIVE**

Classified as hazardous

Hazchem Code 3[Y]E
Packaging Method 3.8.3RT1
Packing Group II
EPG Number 3A1
IERG Number 14

15. REGULATORY INFORMATION

Risk Phrase R11 Highly flammable.
R36/38 Irritating to eyes and skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness and cracking.
R67 Vapours may cause drowsiness and dizziness

Safety Phrase S23 Do not breathe gas/fumes/vapour/spray
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S38 If insufficient ventilation, wear suitable respiratory equipment.
S44 If you feel unwell, contact a doctor or Poisons Information Centre immediately (show the label where possible).
S51 Use only in well ventilated areas.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Poisons Schedule S5

Hazard Category Harmful,Irritant,Highly Flammable

16. OTHER INFORMATION

Contact Person/Point In Australia: RLA Polymers Pty Ltd. - Group Operations Manager: 03 9728 1644 (Business Hours)
For emergency information outside normal business hours, please ring:
SECURITY MONITORING 1300 136102
They will contact the relevant personnel.

The information herein is given in good faith, but subject to the Trade Practices Act 1974, no warranty, expressed or implied, is made.
RL207

Poisons Schedule S5

Hazard Category Harmful,Irritant,Highly Flammable

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.