



## PSA 2300 Pressure Sensitive Adhesive

Solvent-free, aggressive tack adhesive



**PSA 2300 Pressure Sensitive Adhesive** is an aggressive, high solids, releasable, pressure sensitive adhesive formulated to facilitate release and re-bonding of carpet tiles while permanently retaining its tack.





# PSA 2300 Pressure Sensitive Adhesive

Solvent-free, aggressive tack adhesive

## Advantages:

- Solvent free
- Aggressive tack
- Very low odour
- Very quick, strong bond development
- Water and Alkali resistant.
- Highly resistant to vinyl plasticizer migration
- EcoBucket biodegradable within 2 years vs. 50 years for a regular resin bucket.
- Contains MicroSept™ antimicrobial protection

## Uses:

Specially engineered to install cushion backed tiles and roll goods where grid or total glue down installation is recommended. Use for pad-to-floor adhesives for dual bond installations. Compatible with rubber and vinyl pad. Acceptable for use over vinyl asbestos tile or vinyl composition tile when all finishes, including waxes and sealers have been removed.

Not recommended for direct use over existing sheet vinyl, laminated solid vinyl tile, or rubber flooring. Not recommended for application over old cut-back or bituminous or petrochemical based adhesives.

## Coverage:

Approx. 7.8 - 9.2 m<sup>2</sup>/L

## Timing:

This premium adhesive is formulated to facilitate release and re-bonding of carpet tiles while permanently retaining its tack. The dried adhesive will remain on the floor, allowing individual tiles to be lifted out and replaced without substantial loss of adhesive properties.

## Technical Notes:

The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65°- 95° F, and the humidity below 65% for 48 hours prior to, during, and after the testing and installation. See carpet manufacturer's installation instructions and CRI 104 Standard.

Do not use on chemically cleaned subfloors. Any sub floor onto which carpet is to be installed should be carefully inspected to assure that proper bonding of the carpet to the floor can be achieved. Proper adhesion requires that the surface be clean, dry, and free from dust, existing adhesive, paint, old floor finishes, or any foreign material. For tile installations, use a 3/8" nap paint roller and apply in a full spread fashion, taking care to coat all surfaces. Coverage will vary according to the sub-floor type and application method.

Once spread, allow **PSA2300 Adhesive** to dry completely or until the surface becomes tacky to touch. As drying takes place, the adhesive will become a black transparent colour indicating ready to install. Drying speed will vary according to temperature of the sub-floor, porosity of the sub-floor, temperature of the air and components, relative humidity, as well as dryness of the floor and thickness of the application. If the carpet tiles are installed with the adhesive in the wet state, or before sufficient drying has occurred, important release and re-bonding properties will be affected. Carpet tiles may be installed at any time after the spread adhesive becomes tacky.

## Shelf Life:

2 years from manufacturing date.

This adhesive is not photochemically reactive as defined by California rules 102 and 443. VOC content is below that established by the California SCAQMD Rule 1168.

[www.intafloors.com.au](http://www.intafloors.com.au)



For the Smarter Tradesman