



## XL One Seam Sealer

Universal solvent-free seam sealer



**XL One Seam Sealer** is a strong, solvent free adhesive designed for use with most types of carpet backings.





# XL One Seam Sealer

Universal solvent-free seam sealer

## Advantages:

- Superior bond and tensile strength when dry
- Very quick, strong bond development
- Dries clear - contains UV fluorescent tracer
- Highly water resistant when dry
- Does not contain ammonia or solvents
- Non-flammable
- Water cleanup when wet
- Very low odour, ideal for use in schools, public buildings and other areas where odour is a concern.
- Zero calculated VOCs
- CRI Green Label Plus approved
- Manufactured by an ISO 14001:2004 EMS Supplier
- Contains MicroSept™ antimicrobial protection
- Passes water penetration test at 10,000+ cycles on prepared seams

## Uses:

For use with most types of carpet backings, including ActionBac®, vinyl backings, polyolefins, latex unitary, urethane and woven backs. Can be used on direct-glue and double-glue carpet installations to eliminate seam unraveling in commercial and residential installations.

## Coverage:

Approx. 400 linear feet/quart.

## SHELF LIFE:

2 years from manufacturing date, in unopened container. Protect from freezing.

## Directions for Use:

1. Prepare the carpet according to the manufacturer's instructions.
2. Apply continuous bead of seam sealer to the edge of the backing of the first piece of carpet where it meets the carpet pile.
3. Immediately place the edge of the second piece of carpet into contact with the first piece which has the seam sealer on it. To achieve a good bond, it is essential for the two pieces of carpet to have a tight fit, and traffic on the seamed area should be restricted for at least 24 hours.
4. Clean any smears of seam sealer or adhesive with water while material is in the wet state. Dried residue may require the use of an adhesive remover.

This adhesive is tested by the Carpet & Rug Institute and carries the CRI Green Label Plus. This product is not photochemically reactive as defined by California Rules 102 and 443. VOC content is below that established by California SCAQMD Rule 1168.

\* ASTM International, formerly known as the American Society for Testing and Materials: [www.astm.org](http://www.astm.org)

[www.intafloors.com.au](http://www.intafloors.com.au)



For the Smarter Tradesman