



Intafloors IFA550

Outdoor Sporting Adhesive (20L)



INTAFLOORS IFA550 OUTDOOR SPORTING ADHESIVE is an all weather solvent based (flammable) adhesive specifically formulated for the outdoor installation of non-stretch open weave polypropylene backed synthetic grass carpet. Not recommended for urethane and E.V.A. backed carpets.

Intafloors IFA550 Outdoor Sporting Adhesive develops high strength quickly and when cured will withstand unfavourable weather conditions. It will bond securely to cured concrete, asphalt, exterior grade wood and other clean paved surfaces and is ideal for use around swimming pools, balconies, outdoor recreational areas and other applications which are subject to moisture after fixing.



Intafloors IFA550

Outdoor Sporting Adhesive (20L)

Surface Preparation

To be in accordance with The Australian Standard 2455.1: 2007 'Textile Floor Covering installation Practice'. All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease & hydrostatic pressure. All concrete substrate floors should be tested for moisture content, according to the above Australian Standard, prior to undertaking surface priming or installation of floorcovering.

Application

Rough cut and lay out carpet according to manufacturer's instructions. Spread adhesive with the recommended notched trowel. Adhesive must be tacked up before floorcovering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floorcovering into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes rechecking every few minutes thereafter. Complete the installation according to floorcovering manufacturer's instructions. Do not allow heavy traffic for 24 hours.

Do not use in rain or if rain is expected during or immediately after laying.

Clean Up

To clean up equipment and adhesive spills, use cleaner thinner (Flammable).

TYPICAL PROPERTIES

Appearance	Brown
Base	Synthetic rubber
Solids	58% approx
Viscosity	Trowellable mastic
Shelf Life	Up to 1 year in sealed container at 20°C
Flash Point	Less than 0°C

Freezability	Avoid freezing
Packaging	20 litre
Flash Point	Less than 0°C

Trowel size

Smooth backed carpet/smooth substrate: 2.4mm x 2.4mm x 2.4mm 'V' notched. Coverage up to 3.0m²/litre.

Textured backed carpet/rough substrate: 3.2mm x 1.6mm x 3.2mm 'V' notched. Coverage up to 2.0m²/litre.

Heavily ribbed carpet/Rough substrate: 3.2mm x 3.2mm x 3.2mm "U" notched. Coverage up to 1.6m²/litre.

Contains

480ml/litre Liquid Hydrocarbons.

Highly Flammable

Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

First Aid

If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, DO NOT induce vomiting. Give a glass of water.

Safety & Handling

Material Safety Data Sheet is available upon request.

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

ASTM International, formerly known as the American Society for Testing and Materials: www.astm.org

IFA550-20L Outdoor Sporting Adhesive



www.intafloors.com.au

For the Smarter Tradesman