



Intafloors I-Stix

Vinyl Spray Adhesive (22 oz)



INTAFLOORS I-STIX VINYL SPRAY ADHESIVE

is a water-based aerosol adhesive recommended for installations of resilient floor coverings. It is particularly convenient since it can be used in occupied buildings and greatly reduces the handling and application requirements associated with conventional adhesives.





Intafloors I-Stix

Vinyl Spray Adhesive (22 oz)

Advantages

- Easy to Use.
- Non-flammable product
- Non-flammable propellant
- Simple spray application eliminates trowels and rollers
- Virtually Odour Free
- No solvents or hazardous chemicals
- Outstanding water resistance when dry (has outstanding water and plasticizer resistance)
- Highly aggressive grab and shear strength – 10-15% high than standard trowel able adhesive.
- CRI Green Label Plus approved and SCS Floor Score Certified
- Can be installed over porous and non-porous substrates.
- Normal traffic may be allowed as soon as the installation, finishing and clean-up are complete. No down time once installed in an occupied buildings

Application

Shake can well before each use. Point can downwards, press the side of the nozzle tip as

you slowly walk back and forth. Do not use a sweeping motion as this will create uneven

coverage. Clean up drips. When using for LVT or LVP be sure to achieve full coverage.

When using on a non-porous substrate, a lighter application will be necessary.

Intafloors I-Stix may also be used for vinyl cove base repairs. First be sure that wall is clean and dry, and remove any loose wall paper or paint.

Safety & Clean Up

Wet adhesive overspray or drips should be cleaned with soap and water on a clean

cloth. Dried adhesive may require the use of a solvent

adhesive cleaner. Between uses,

clean the spray tip immediately with a clean wet cloth to prevent accumulation of dried

adhesive. Empty aluminum spray cans should be relieved of excess pressure and recycled

or disposed of in accordance with local requirements.

Coverage

A coverage of 150 square feet per can – 14 square meters.

First Aid

Avoid contact with eyes and skin. For eye contact, flush thoroughly with water for

15 minutes and get immediate medical attention. For skin contact, wash area with

soap and water. If swallowed, do not induce vomiting; get medical attention immediately.

If inhaled, remove person to fresh air; for difficulty breathing, get immediate medical attention.

Open Time

Allow the adhesive to become tacky to the touch with little or no transfer

to fingers when lightly touched. Open time will vary depending on the adhesive coverage

and the ambient conditions. Working time for the adhesive should not exceed 4 hours

Safety & Handling

Material Safety Data Sheet is available upon request.

Shelf Life

2 years from manufacturing date.

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.



www.intafloors.com.au

For the Smarter Tradesman